



PetroCote Bitumen Primer

Product Description

PetroCote Bitumen Primer is an integral component of the PCS PetroCote System.
PetroCote Bitumen Primer is a blend of cut back bitumen, dispersed in solvent.

Product Characteristics

PetroCote Bitumen Primer is formulated for stability and plasticity over a wide temperature range.
PetroCote Bitumen Primer is a quick drying, hi-tack coating which profiles minor surface imperfections and enables uniform adhesion of PetroCote Tape to the cleaned substrate.

Product Uses

Pipeline: Above ground or below ground.
Other: Joint sealing for reinforced concrete pipes and culverts.

Product Application

PetroCote Bitumen Primer is applied by brush to fill surface imperfections and coat the area to be wrapped. Primer is tack dry in 3-5 minutes. Wrapping should occur within 3 hours of priming or fresh primer should be applied.

Product Properties

Property	Value
Specific Gravity	0.91 (average)
Drying Time	3-5 minutes
Coverage	9 m ² /L (average)
Application Temperature	0 to +50 °C
Service Temperature	-20 to +65 °C
Shelf Life	Minimum 24 months @ 25 °C

*Note that coverage is determined by surface profile. Heavily pitted substrates will require more primer compared to a smooth substrate. Concrete may require two coats, depending on porosity.

Product Packaging

Part No.	Width	Length	Carton Qty
PCT004	4 Litre	Tin	4 Tins/Carton
PCT020	20 Litre	Drum	1 Drum
PCT200	200 Litre	Drum	1 Drum

IMPORTANT

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use, prior to purchase.