



Round Butyl Strip

Product Description

Round Butyl Strip is custom designed for the sealing of segmented concrete pipes and manhole units.

Round Butyl Strip is a blend of synthetic rubbers formed from isobutylene and isoprene. Adhesion is enhanced with appropriate tackifiers.

Product Characteristics

Round Butyl Strip is formulated for stability and plasticity over a wide temperature range.

Round Butyl Strip will not shrink or oxidise over time. Round Butyl Strip conforms fully with the requirements of ASTM C990M-09 Pre-Formed Flexible Butyl Joint Sealant.

Product Uses

Concrete: Sealing mating joint surfaces.
Steel: Joint profiling prior to wrapping.

Product Application

Brush surface clean of dust.

Porous surfaces may be primed with PetroCote Butyl Primer. Lay strip in joint in a continuous coil. Butt join ends.

Product Properties

Property	Value
Hardness (00 Durometer)	70 (Average)
Specific Gravity	1.1 (Average)
Application Temperatures	-10 to +50 °C
Service Temperature	-10 to +75 °C
Shelf Life	36 Months @ 25 °C

Product Packaging

Part No	Diameter	Length	Carton Qty	Ctns /Pallet
JGR12	12mm	3.6 m	5 Coils	500
JGR15	15mm	3.6 m	5 Coils	500
JGR17 - 2.2	17mm	2.2 m	5 Coils	500
JGR17 - 3.6	17 mm	3.6 m	5 Coils	500
JGR20	20mm	3.6 m	5 Coils	500
JGR25	25mm	3.6 m	5 Coils	500

IMPORTANT

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use, prior to purchase.