



SteelGard 200 UV Tape

Product Description

SteelGard 200 UV Tape is a butyl rubber self-adhesive anti corrosion tape with a UV resistant aluminium backing film.

Product Characteristics

SteelGard 200 UV Tape exhibits exceptional adhesion to metals, epoxies and plastics.

SteelGard 200 UV Tape exhibits exceptional resistance to temperature extremes.

The plastic nature of the product allows it to comfortably accommodate both substrate vibration and movement.

Product Uses

Steel: Corrosion protection and sealing of pipework and steelwork.

Buildings: Flashing and waterproofing of structures.

Product Application

Refer to the PCS: Consultant Specification Guide – SteelGard 200 System

Product Properties

Property	Test Method	Value
Thickness	ASTM D751	1.0 mm (Average)
UV Resistance	-	Resistant
Tensile Strength	EN 12311-1	3 N/mm (Average)
Elongation at Break	EN 12311-1	> 25%
Vertical Flow	ISO 7390	< 10 mm
Application Temperature		0 to +50 °C
Service Temperature		-40 to +100 °C

Product Packaging

Part No.	Width	Unit	Carton Qty
BSG2050	50mm	10m	24 rolls
BSG2075	75mm	10m	18 rolls
BSG2100	100mm	10m	12 rolls
BSG2200	200mm	10m	6 rolls
BSG2300	300mm	10m	4 rolls

Other sizes are available on request.

IMPORTANT

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use, prior to purchase.