



# MarineGard Primer

## Product Description

MarineGard Primer is an integral component of the MarineGard Systems.

MarineGard Primer is a blend of neutral petrolatum compounds, inert siliceous fillers and water displacing agents.

## Product Characteristics

- stable in composition and plasticity over a wide temperature range
- non-hardening and non-cracking
- accommodates vibration and movement of substrate
- highly resistant to mineral acids, alkalis and salts
- will adhere and remain attached to clean, sound, wet or dry surfaces
- displaces surface moisture and pacifies surface oxides
- formulated to provide protection against sulfate reducing bacteria (independent test report available)
- can be applied under water

## Product Uses

Fills surface imperfections and ensures intimate contact between MarineGard Tape and the substrate being protected.

Corrosion protection, sealing and water proofing of surfaces above and below water.

An integral component of the PCS MarineGard Systems for the long term protection of wharf and riser piles particularly in splash and tidal zones.

## Product Application

Refer to the PCS: Consultant Specification Guide – PCS MarineGard System.

## Product Properties

Property	Test Method	Value
Density	ASTM D1475	0.90 kg/L
Uncut Cone Penetration	ASTM D937	210 ± 30 dmm
Application Temperatures		-5 to + 45°C
Service Temperature		-25 to + 50°C
Maximum Temperature		+55°C

## Product Packaging

Part No	Size	Carton Qty
PPM04	4L	2 tubs
PPM20	20L	1 drum

### IMPORTANT

All statements and data presented herein are given in good faith and believed to be appropriate and reliable. It is given without express or implied warrant or guarantee. Potential users of our materials are urged to conduct confirmatory trials to satisfy themselves as to the suitability of the selected product for their particular end use, prior to purchase.